



PFG ( W )  
镀锌钢辊 /Galvanized roller



PFG  
加长可调橡胶辊/Extension rubber roller



PFG  
宽腿加长辊筒/Widen leg roller

型号/Model	前轮固定/ Fixed Front Wheel	(PFG2085)	(PFG2120)	PFG4085	PFG4120	PFG4150
	前轮万向/ Universal Front Wheel	(PFG2085W)	(PFG2120W)	PFG4085W	PFG4120W	PFG4150W
最大载重/Max.Capacity	kg	200	200	400	400	400
辊筒最大升高/ Max. Roller Height	mm	870	1200	870	1200	1500
辊筒最低高度/ Min. Roller Height	mm	180/220	180/220	180/220	180/220	180/220
支腿高度(固定轮)/ Leg Height (fixed wheels)	mm	80	80	80	80	80
支腿高度(万向轮)/ Leg Height (Universal wheels)	mm	110	110	120	120	120
适用工件最大直径/ Max Diameter of workpiece	mm	Φ 100 × Φ 300		Φ 200 × Φ 600		
辊筒尺寸/ Roller Size	mm	Φ 76 × 500	Φ 76 × 500	Φ 76 × 550	Φ 76 × 550	Φ 76 × 550
辊筒长度	mm	500~(800)		550~(800)		
辊筒中心距/Roller Center Length	mm	120	120	180 (240)	180 (240)	180 (240)
辊筒材料/ Roller Material	mm	橡胶(PU,镀锌钢,不锈钢)/ Rubber (PU, Galvanized Steel, Stainless Steel)				
辊筒可调中心距离/Adjustable center distance	mm	(100~250)				
外形尺寸 / Overall Size (L × W × H)	mm	680 × 580 × 1030	680 × 580 × 1380	780 × 630 × 1070	780 × 630 × 1420	780 × 630 × 1720
前轮直径 / Front Wheel Diameter	mm	Φ 75 (固定/ Fixed)/ Φ 75 (万向/ Universal)				
后轮直径 / Rear Wheel Diameter	mm	Φ 125/ Φ 150				
工作次数/ Pump Stroke		14	21	30	45	58
净重/Net Weight	kg	53	58	72	78	85

• 括号内型号、尺寸，需按规定数量特制

Size in brackets are special made and customized for specified quantities